

**UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS**  
GCE Advanced Subsidiary Level and GCE Advanced Level

**MARK SCHEME for the May/June 2012 question paper**  
**for the guidance of teachers**

**9702 PHYSICS**

**9702/22**

Paper 2 (AS Structured Questions), maximum raw mark 60

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

- Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2012 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2012	9702	22

- 1 (a)  $\frac{V}{t} = \frac{\pi P r^4}{8 C l}$   
 $C = [\pi \times 2.5 \times 10^3 \times (0.75 \times 10^{-3})^4] / (8 \times 1.2 \times 10^{-6} \times 0.25)$   
 $= 1.04 \times 10^{-3} \text{ N s m}^{-2}$  C1  
A1 [2]
- (b)  $4 \times \%r$  C1  
 $\%C = \%P + 4 \times \%r + \%V/t + \%l$   
 $= 2\% + 5.3\% + 0.83\% + 0.4\% (= 8.6\%)$  A1  
 $\Delta C = \pm 0.089 \times 10^{-3} \text{ N s m}^{-2}$  A1 [3]
- (c)  $C = (1.04 \pm 0.09) \times 10^{-3} \text{ N s m}^{-2}$  A1 [1]
- 2 (a) (i)  $v^2 = u^2 + 2as$   
 $= (8.4)^2 + 2 \times 9.81 \times 5$  C1  
 $= 12.99 \text{ m s}^{-1}$  (allow 13 to 2 s.f. but not 12.9) A1 [2]
- (ii)  $t = (v - u) / a$  or  $s = ut + \frac{1}{2}at^2$   
 $= (12.99 - 8.4) / 9.81$  or  $5 = 8.4t + \frac{1}{2} \times 9.81t^2$  M1  
 $t = 0.468 \text{ s}$  A0 [1]
- (b) reasonable shape M1  
suitable scale A1  
correctly plotted 1<sup>st</sup> and last points at (0,8.4) and (0.88 – 0.96,0)  
with non-vertical line at 0.47 s A1 [3]
- (c) (i) 1. kinetic energy at end is zero so  $\Delta KE = \frac{1}{2}mv^2$  or  $\Delta KE = \frac{1}{2}mu^2 - \frac{1}{2}mv^2$  C1  
 $= \frac{1}{2} \times 0.05 \times (8.4)^2$   
 $= (-) 1.8 \text{ J}$  A1 [2]
2. final maximum height  $= (4.2)^2 / (2 \times 9.8) = (0.9 \text{ (m)})$   
change in PE  $= mgh_2 - mgh_1$  C1  
 $= 0.05 \times 9.8 \times (0.9 - 5)$  C1  
 $= (-) 2.0 \text{ J}$  A1 [3]
- (ii) change is – 3.8 (J) B1  
energy lost to ground (on impact) / energy of deformation of the ball /  
thermal energy in ball B1 [2]
- 3 (a) (a) A body continues at rest or constant velocity unless acted on by a resultant (external) force B1 [1]
- (b) (i) constant velocity/zero acceleration and therefore no resultant force M1  
no resultant force (and no resultant torque) hence in equilibrium A1 [2]
- (ii) component of weight  $= 450 \times 9.81 \times \sin 12^\circ (= 917.8)$  C1  
tension  $= 650 + 450g \sin 12^\circ = (650 + 917.8)$  C1  
 $= 1600 (1570) \text{ N}$  A1 [3]

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2012	9702	22

- (iii) work done against frictional force or friction between log and slope  
output power greater than the gain in PE / s M1  
A1 [2]
- 4 (a) total resistance = 20 (k $\Omega$ ) C1  
current = 12 / 20 (mA) or potential divider formula C1  
p.d. = [12 / 20]  $\times$  12 = 7.2V A1 [3]
- (b) parallel resistance = 3 (k $\Omega$ ) C1  
total resistance 8 + 3 = 11 (k $\Omega$ ) C1  
current = 12 / 11  $\times$  10<sup>3</sup> = 1.09  $\times$  10<sup>-3</sup> or 1.1  $\times$  10<sup>-3</sup> A A1 [3]
- (c) (i) LDR resistance decreases M1  
total resistance (of circuit) is less hence current increases A1 [2]
- (ii) resistance across XY is less M1  
less proportion of 12V across XY hence p.d. is less A1 [2]
- 5 (a)  $E = \text{stress} / \text{strain}$  B1 [1]
- (b) (i) 1. diameter / cross sectional area / radius B1 [1]  
2. original length
- (ii) measure original length with a metre ruler / tape B1  
measure the diameter with micrometer (screw gauge) B1 [2]  
*allow digital vernier calipers*
- (iii) energy =  $\frac{1}{2} Fe$  or area under graph or  $\frac{1}{2} kx^2$  C1  
 $= \frac{1}{2} \times 0.25 \times 10^{-3} \times 3 = 3.8 \times 10^{-4} \text{ J}$  A1 [2]
- (c) straight line through origin below original line M1  
line through (0.25, 1.5) A1 [2]
- 6 (a) two waves travelling (along the same line) in opposite directions overlap/meet M1  
same frequency / wavelength A1  
resultant displacement is the sum of displacements of each wave /  
produces nodes and antinodes B1 [3]
- (b) apparatus: source of sound + detector + reflection system B1  
adjustment to apparatus to set up standing waves – how recognised B1  
measurements made to obtain wavelength B1 [3]
- (c) (i) at least two nodes and two antinodes A1 [1]
- (ii) node to node =  $\lambda / 2 = 34 \text{ cm}$  (allow 33 to 35 cm) C1  
 $c = f\lambda$  C1  
 $f = 340 / 0.68 = 500$  (490 to 520) Hz A1 [3]

Page 4	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2012	9702	22

- 7 (a)  $W = 1$  and  $X = 0$  A1 [1]  
 $Y = 2$  A1 [1]  
 $Z = 55$  A1 [1]
- (b) explanation in terms of mass – energy conservation B1  
energy released as gamma or photons or kinetic energy of products or  
em radiation B1 [2]