

CAMBRIDGE INTERNATIONAL EXAMINATIONS

Cambridge International Advanced Subsidiary and Advanced Level

MARK SCHEME for the May/June 2015 series

9702 PHYSICS

9702/43

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2015 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

Section A

- 1 (a) (gravitational) force proportional to product of masses and inversely proportional to square of separation
reference to *either* point masses *or* particles *or* 'size' much less than separation
- M1
A1 [2]
- (b) gravitational force provides/is the centripetal force
 $GM_N m / r^2 = m r \omega^2$ (or $m v^2 / r$)
 $2\pi / T$ (or $v = 2\pi r / T$) leading to $GM_N = 4\pi^2 r^3 / T^2$
- B1
M1
A1 [3]
- (c) $M_N / M_U = (3.55 / 5.83)^3 \times (13.5 / 5.9)^2$
 x^3 factor correct
 T^2 factor correct
ratio = 1.18 (allow 1.2)
- C1
C1
A1
- alternative method:* mass of Neptune = 1.019×10^{26} kg
mass of Uranus = 8.621×10^{25} kg
ratio = 1.18
- (C1)
(C1)
(A1) [3]
- 2 (a) (sum of) potential energy and kinetic energy of molecules/atoms/particles
mention of random motion/distribution
- M1
A1 [2]
- (b) (i) $pV = nRT$
either at A, $1.2 \times 10^5 \times 4.0 \times 10^{-3} = n \times 8.31 \times 290$
or at B, $3.6 \times 10^5 \times 4.0 \times 10^{-3} = n \times 8.31 \times 870$
 $n = 0.20$ mol
- C1
A1 [2]
- (ii) $1.2 \times 10^5 \times 7.75 \times 10^{-3} = 0.20 \times 8.31 \times T$ or $T = (7.75 / 4.0) \times 290$
 $T = 560$ K
(Allow tolerance from graph: $7.7-7.8 \times 10^{-3} \text{ m}^3$)
- C1
A1 [2]
- (c) temperature changes/decreases so internal energy changes/decreases
volume changes (at constant pressure) so work is done
- B1
B1 [2]
- 3 (a) (numerically equal to) quantity of (thermal) energy/heat to change state/phase of unit mass
at constant temperature
(allow 1/2 for definition restricted to fusion or vaporisation)
- M1
A1 [2]
- (b) (i) at 70 W, $\text{mass s}^{-1} = 0.26 \text{ g s}^{-1}$
at 110 W, $\text{mass s}^{-1} = 0.38 \text{ g s}^{-1}$
- A1
A1 [2]

Page 3	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

- (ii) 1. $P + h = mL$ or substitution of one set of values
 $(110 - 70) = (0.38 - 0.26)L$
 $L = 330 \text{ Jg}^{-1}$ C1
C1
A1 [3]
2. either $70 + h = 0.26 \times 330$
or $110 + h = 0.38 \times 330$ C1
 $h = 17/16/15 \text{ W}$ A1 [2]
- 4 (a) (i) frequency at which object is made to vibrate/oscillate B1 [1]
- (ii) frequency at which object vibrates when free to do so B1 [1]
- (iii) maximum amplitude of vibration of oscillating body
when forced frequency equals natural frequency (of vibration) B1
B1 [2]
- (b) e.g. vibration of quartz/piezoelectric crystal (*what is vibrating*) M1
either for accurate timing
or maximise amplitude of ultrasound waves (*why it is useful*) A1 [2]
- (c) e.g. vibrating metal panels (*what is vibrating*) M1
either place strengthening struts across the panel
or change shape/area of panel (*how it is reduced*) A1 [2]
- 5 (a) (magnitude of electric field strength is the potential gradient B1
use of gradient at $x = 4.0 \text{ cm}$ M1
gradient $= 4.5 \times 10^4 \text{ NC}^{-1}$ (*allow* $\pm 0.3 \times 10^4$) A1
- or
- $V = \frac{Q}{4\pi\epsilon_0 x}$ and $E = \frac{Q}{4\pi\epsilon_0 x^2}$ leading to $E = \frac{V}{x}$ (B1)
- $E = 1.8 \times 10^3 / 0.04$ (M1)
 $= 4.5 \times 10^4 \text{ NC}^{-1}$ (A1) [3]
- (b) (i) $3.6 \times 10^3 \text{ V}$ A1 [1]
- (ii) capacitance $= Q/V$ C1
 $= (8.0 \times 10^{-9}) / (3.6 \times 10^3)$
 $= 2.2 \times 10^{-12} \text{ F}$ A1 [2]
- 6 (a) (i) gravitational B1 [1]
- (ii) gravitational and electric B1 [1]
- (iii) magnetic and one other field given
magnetic, gravitational and electric B1
B1 [2]

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

- (b) (i) out of (plane of) paper/page (*not* “upwards”) B1 [1]
- (ii) $B = mv/qr$ C1
 $= (3.32 \times 10^{-26} \times 7.6 \times 10^4)/(1.6 \times 10^{-19} \times 6.1 \times 10^{-2})$ C1
 $= 0.26 \text{ T}$ A1 [3]
- (c) sketch: semicircle with diameter $< 12.2 \text{ cm}$ B1 [1]
- 7 (a) can change (output) voltage efficiently *or* to suit different consumers/appliances by using transformers B1
B1 [2]
- (b) for same power, current is smaller B1
 less heating in cables/wires
or thinner cables possible
or less voltage loss in cables B1 [2]
- 8 (a) (i) $p = h/\lambda$
 $= (6.63 \times 10^{-34})/(6.50 \times 10^{-12})$ C1
 $= 1.02 \times 10^{-22} \text{ N s}$ A1 [2]
- (ii) $E = hc/\lambda$ *or* $E = pc$
 $= (6.63 \times 10^{-34} \times 3.00 \times 10^8)/(6.50 \times 10^{-12})$ C1
 $= 3.06 \times 10^{-14} \text{ J}$ A1 [2]
- (b) (i) $0.34 \times 10^{-12} = (6.63 \times 10^{-34})/(9.11 \times 10^{-31} \times 3.0 \times 10^8) \times (1 - \cos \theta)$ C1
 $\theta = 30.7^\circ$ A1 [2]
- (ii) deflected electron has energy M1
 this energy is derived from the incident photon A1
 deflected photon has less energy, longer wavelength (so $\Delta\lambda$ always positive) B1 [3]
- 9 (a) nucleus/nuclei emits M1
 spontaneously/randomly A1
 α -particles, β -particles, γ -ray photons A1 [3]
- (b) (i) $N - \Delta N$ A1 [1]
- (ii) $\Delta N/\Delta t$ A1 [1]
- (iii) $\Delta N/N$ A1 [1]
- (iv) $\Delta N/N\Delta t$ A1 [1]
- (c) graph: smooth curve in correct direction starting at (0,0) M1
 n at $2t_{1/2}$ is 1.5 times that at $t_{1/2}$ ($\pm 2 \text{ mm}$) A1 [2]

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

Section B

- 10 (a) (i)** (potential =) $1.2/(1.2 + 4.2) \times 4.5 = +1.0\text{V}$ A1 [1]
- (ii)** (for $V_{\text{IN}} > 1.0\text{V}$) $V^+ > V^-$ B1
 output (of op-amp) is +5 V or positive M1
 diode conducts giving +5 V across R or V_{out} is +5 V A1
- (for $V_{\text{IN}} < 1.0\text{V}$) output of op-amp -5V /negative so diode does not conduct,
 giving $V_{\text{out}} = 0$ or 0V across R A1 [4]
- (b) (i)** square wave with maximum value +5 V and minimum value 0 M1
 vertical sides in correct positions and correct phase A1 [2]
- (ii)** re-shaping (digital) signals/regenerator (amplifier) B1 [1]
- 11 (a)** change/increase/decrease anode/tube voltage B1
 electrons striking anode have changed (kinetic) energy/speed B1
 X-ray/photons/beam have different wavelength/frequency B1 [3]
- (b) (i)** $I = I_0 e^{-\mu x}$ B1 [1]
- (ii)** contrast is difference in degree of blackening (of regions of the image) B1
 μ (very) similar so similar absorption of radiation (for same thickness) so little contrast A1 [2]
- 12 (a) (i)** loudspeaker/doorbell/telephone etc. B1 [1]
- (ii)** television set/audio amplifier etc. B1 [1]
- (iii)** satellite/satellite dish/mobile phone etc. B1 [1]
- (b)** e.g. lower attenuation/fewer repeaters
 more secure
 less prone to noise/interference
 physically smaller/less weight
 lower cost
 greater bandwidth
 (any two sensible suggestions, 1 each) B2 [2]
- (c) (i)** ratio = $25 + (62 \times 0.21)$ C1
 = 38 dB A1 [2]
- (ii)** ratio/dB = $10 \lg(P_2/P_1)$ C1
 $38 = 10 \lg(P/\{9.2 \times 10^{-6}\})$
- $P = 58 \text{ mW}$ or $5.8 \times 10^{-2} \text{ W}$ A1 [2]
 (allow 1/2 for missing 10 in equation)

Page 6	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

- 13 (a) (i) to align nuclei/protons
to cause Larmor/precessional frequency to be in r.f. region
- B1
B1 [2]
- (ii) Larmor/precessional frequency depends on (applied magnetic) field strength
knowing field strength enables (region of precessing) nuclei to be located
by knowing the frequency
- B1
M1
A1 [3]
- (b) $E = 2.82 \times 10^{-26} \times B$
 $6.63 \times 10^{-34} \times 42 \times 10^6 = 2.82 \times 10^{-26} \times B$
- C1
- $B = 0.99 \text{ T}$
- A1 [2]