Question Number	Scheme	М	arks
1	T (a) R (\rightarrow): $T \cos 60 = 50 \cos 30$	M1	A1
	$T = \underline{86.6 \text{ N}}$		A1 (3)
	(b) $R(\uparrow)$: $W = 50 \sin 30 + T \cos 30$	M1	A1
	= <u>100 N</u>		A1 (3)
	or R (to <i>BC</i>): $W \cos 60 = 50$	M1	A1
	$W = \underline{100 \text{ N}}$		A1 (3)
	 (a) M1 for a valid equation in T only Treat use of tan 30/60 (e.g. tan 30 = T/50) as invalid equation unless there is a tria Forces 	angle o	f
	(b) <i>M1</i> for a valid equation involving <i>W</i> (and <i>T</i> if necessary)		
	for first A1 in (i), allow for using their T (i.e. effectively f.t.) Accept each answer as awrt.		

Question Number	Scheme	Marks
2	(a) $v = u + at$: $9.5 = 5 + 1.5a \Rightarrow a = 3$	M1 A1 ↓
	Hence $v^2 = 5^2 + 2 \times 3 \times 24$	M1
	$= 169 \implies v = 13 \text{ m s}^{-1}$ (*)	A1 (4)
	(b) $I = mv - mu': -30 = 2(v - 13) \implies v = (-) 2 \text{ m s}^{-1}$	M1 A1
	In direction of CA (o.e.)	A1 (3)
	(a) 2 nd M1 for equation in v (and numbers) only Final A1 is cso	
	 (b) M1 for valid impulse = momentum change equn with 3 non-zero terms includi A1 for '30' and '13' with same sign A1 for direction as 'CB' or anything convincing! 	ng '30' and '13'
	NB both A's in (b) are cao = cso!	

Question Number	Scheme	Marks
3	$u \longrightarrow 2 \text{ kg}$ 4 kg CLM: $2u = -2v + 4w$ $v \longleftarrow W$ Using $w = 3v$ ($\Rightarrow 2u = -2v + 12v$) and solve	M1 A1 ↓
	$v \leftarrow w$ Using $w = 3v$ ($\Rightarrow 2u = -2v + 12v$) and solve $\Rightarrow v = \frac{1}{5}u$ (*)	M1 A1 cso (4)
	(b) $10 = 2a \implies a = 5 \text{ m s}^{-2}$	B1
	$0 = \frac{1}{25}u^2 - 2 \times 5 \times 1.6$	M1 A1√ ↓
	$\rightarrow u = 20 \text{ m s}^{-1}$	M1 A1 (5)
	(a) 1 st M1 for valid CLM equn 2 nd M1 for correct equn for 'v' and 'w' and solving for v or w. Final A1 is cso (dropping u and reinserting loses last A1)	
	(b) Allow B1 for $a = \pm 5$ M1 for using ' $v^2 = u^2 + 2as$ ' with $v = 0$ and with a value for a A1 f.t. on their a (provided this is not g), but signs must be correct	
	SC For using u instead of $u/5$ ($\rightarrow u = 4$), allow M1 A0 M0.	
	Energy: $\frac{1}{2} \times 2 \times (\frac{u}{5})^2 = 10 \times 1.6$ M1 A1 A1	
	$\rightarrow u = 20$ dep M1 A1	

Question Number	Scheme	Marks
4	(a) M(D): $20g \times 1.5 + 10g \times 1 = R_B \times 3$	M1 A1 ↓
	$\Rightarrow \qquad R_B = \frac{40g/3}{\approx 131 \text{ or } 130 \text{ N}}$	↔ M1 A1 (4)
	[NB For moments about another point, allow M1 A1 for moments equation dimens correct and with correct number of terms; second M1 is for complete method to find R	
	(b) $R(\uparrow)$: $R_D + 40g/3 = 20g + 10g$	M1 A1√
	$\Rightarrow R_D = 50g/3 \approx 163 \text{ or } 160 \text{ N}$	A1 (3)
	or M(B): $20g \times 1.5 + 10g \times 2 = R_D \times 3$	M1 A1
	\Rightarrow $R_D = 50g/3 \approx 163 \text{ or } 160 \text{ N}$	A1 (3)
	[NB For moments about another point, allow M1 for a complete method to find R_D , A1 equation for R_D .]	for a correct
	(c) $R_B = 0$	M1
	M(D): $20g \times x = 10g \times 1$	M1 A1
	x = DF = 0.5 m	A1 (4)
	For weight/mass confusion, A0 A0 in (a) but allow f.t. in (b) (ans $50/3 = 16.7$)	
	General rule of deducting max. 1 per question for > 3 s.f	
	 (c) 2nd M1: must have correct no. of non=zero terms, and equation in x only If use value(s) of R's from (a) or (b): M0. 	

www.dynamicpapers.com

Question Number	Scheme	Ма	arks
5	(a) $R = 400g \cos 15^{\circ} (\approx 3786 \text{ N})$ F = 0.2R used		31 31
	$400g \bullet T + 0.2R = 400g \sin 15^{\circ}$	M1 ↓	A1
	<i>T</i> ≈ <u>257 or 260 N</u>	₩ M1	A1 (6)
	(b) $400g \sin 15^\circ - 0.2 \times 400g \cos 15^\circ = 400a$	M1	A1
	a = 0.643()		A1
	$50 = \frac{1}{2} \times 0.643 \times t^2$	M1	A1√
	$t = \frac{12.5 \text{ or } 12 \text{ s}}{12.5 \text{ or } 12 \text{ s}}$		A1 (6)
	General rule again about > 3 sf		
	Weight/mass confusion: treat as MR [\rightarrow T = 26.3/26; a = 0.0656; t = 39(.0)]		
	(b) Allow $a = 0.64$		
	(Final M1 not dependent but requires an attempt to find an a which is not assumed to be	g)	

Question Number	Scheme	Marks
6	(a) Direction of $\mathbf{v} = (7\mathbf{i} - 7.5\mathbf{j}) - (4\mathbf{i} - 6\mathbf{j}) = 3\mathbf{i} - 1.5\mathbf{j}$	M1 ↓
	$\tan \theta = \frac{1.5}{3} = 0.5 \Rightarrow \theta = 26.565$	M1 A1
	Bearing = <u>117</u> (accept awrt)	A1 (4)
	(b) $\mathbf{v} = (3\mathbf{i} - 1.5\mathbf{j}) \div \frac{3}{4} = 4\mathbf{i} - 2\mathbf{j}$	B1
	s = (4i - 6j) + t(4i - 2j)	M1 A1√ (3)
	(c) At 1015 s = $(4i - 6j) + \frac{5}{4} (4i - 2j) (= 9i - 8.5j)$	M1 A1
	m = 0.25 (pi + qj)	B1 ↓
	$\mathbf{s} = \mathbf{m} \Rightarrow \underline{p} = 36, \ q = -34$	M1 A1, A1 (6)
	 (a) Forming direction for v can be either way round. M1 for tan = 'i/j' or 'j/i' A1 for 26.6 or 63.4 (awrt) from a correct direction for v A1 cao 	
	(b) Allow B1 for correct vector for \mathbf{v} wherever seen (e.g. in (a))	
	(c) line 1: or $(7i - 7.5j) + \frac{1}{2}(4i - 2j) = \dots$ $1^{st} M1$ allow for a valid attempt with a value of t. $2^{nd} M1$ using $s = m$ and equating at least one coefficient	

www.dynamicpapers.com

Question Number	Scheme	Marks
7	$ \begin{array}{c} F_1 \\ & F_2 \\ & 4g \end{array} \xrightarrow{F_2} & 6g \end{array} \xrightarrow{R_2} 40 $	
	(a) $F_1 = \frac{2}{7} \times 4g$ (= 11.2) or $F_2 = \frac{2}{7} \times 6g$ (= 16.8)	B1
	System: $40 - \frac{2}{7} \times 4g - \frac{2}{7} \times 6g = 10a$ (equn in <i>a</i> and not <i>T</i>)	M1 A1
	$\Rightarrow \underline{a = 1.2 \text{ m s}^{-2}} (*)$	A1 (4)
	(b) <i>P</i> : $T - \frac{8}{7}g = 4 \times 1.2$ or <i>Q</i> : $40 - T - \frac{12}{7}g = 6 \times 1.2$	M1 A1
	\Rightarrow T = <u>16 N</u>	A1
	(c) Accelerations of <i>P</i> and <i>Q</i> are same	(3) B1 (1)
	(d) $v = 1.2 \times 7 = 8.4$	(1) B1
	<i>P</i> : (-) $\frac{8}{7}g = 4a \implies a = (-) \frac{2}{7}g = 2.8$	M1 A1 ↓
	$0 = 8.4 - 2.8t \implies t = 3 \text{ s}$ (*)	M1 A1 (5)
	(e) Q: $40 - \frac{12}{7}g = 6a$ ($\Rightarrow a \approx 3.867$)	M1 A1
	$v = 8.4 + 3.867 \text{ x } 3 = 20 \text{ m s}^{-1}$	↓ M1 A1 (4)
	 (a) 1st A1 requires values for the F's. (Allow M1 with just 'F''s) (b) Allow M1 A1 for one of these equations wherever seen (e.g. in (a)) 	(+)
	(c) extra statement about tensions being equal (with the correct ans): B0	
	(d) allow verification	
	No g: allow 1 st M1 in each of parts (a), (b), (d), (e) as f.t. but other A's are cao	