

**CAMBRIDGE INTERNATIONAL EXAMINATIONS**

Cambridge International Advanced Subsidiary and Advanced Level

**MARK SCHEME for the October/November 2014 series**

**9702 PHYSICS**

**9702/21**

Paper 2 (AS Structured Questions), maximum raw mark 60

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2014 series for most Cambridge IGCSE<sup>®</sup>, Cambridge International A and AS Level components and some Cambridge O Level components.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	21
1	(a) temperature current (allow amount of substance and luminous intensity)	B1 B1	[2]
	(b) base units of force constant: $\text{kg m s}^{-2} \text{m}^{-1}$ or $\text{kg s}^{-2}$ base units of time and mass: s and kg base units of C: $\text{s} (\text{kg s}^{-2} / \text{kg})^{1/2}$ cancelling to show no units	B1 C1 B1	[3]
2	(a) pressure = force / area (normal to the force) [clear ratio essential]	B1	[1]
	(b) (i) $P = mg / A = (5.09 \times 9.81) / A$ $A = (\pi d^2 / 4) = \pi \times (9.4 \times 10^{-2})^2 / 4 (= 0.00694 \text{ m}^2)$ $P = 49.93 / 0.00694$ $= 7200 (7195) \text{ Pa}$ (minimum of 2 s.f. required)	C1 C1 A1	[3]
	(ii) $\Delta P / P = \Delta m / m + 2\Delta d / d$ $= 0.01 / 5.09 + (2 \times 0.1) / 9.4 (= 0.0020 + 0.021 \text{ or } 2.3\%)$ $\Delta P = 170 (165 \text{ to } 167) \text{ Pa}$	C1 C1 A1	[3]
	(iii) $P = 7200 \pm 200 \text{ Pa}$	A1	[1]
3	(a) <u>random</u> error (in the measurements) of the length OR resistance	B1	[1]
	(b) gradient = $(3.6 - 1.9) / (0.8 - 0.4)$ $= 4.25$	C1 A1	[2]
	(c) $R = \rho l / A$ $\rho = \text{gradient} \times \text{area} = 4.25 \times 0.12 \times 10^{-6}$ $= 5.1(0) \times 10^{-7} \Omega \text{ m}$	C1 C1 A1	[3]
	(d) resistance decreasing with increasing area correct shape with curve being asymptote to both axes	B1 B1	[2]

Page 3	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	21
4	(a) (i) acceleration = $(v - u) / t$ or $(12 - 0.5) / 4$ = $(12 - 0.5) / 4 = 2.9$ (2.875) (= approximately $3 \text{ ms}^{-2}$ )		C1 M1 [2]
	(ii) $x = (u + v)t / 2$ = $[(12 + 0.5) \times 4] / 2$ = 25 m		C1 A1 [2]
	(iii) line with increasing gradient non-zero gradient at origin		M1 A1 [2]
	(b) (i) weight down slope = $2 \times 9.81 \times \sin 25^\circ = 8.29 / 8.3$		M1 [1]
	(ii) ( $F = ma$ ) $8.3 - F_R = 2 \times 2.9$ $F_R = 2.5$ (2.3 if 3 used for a) N		C1 A1 [2]
5	(a) (i) change in kinetic energy = $\frac{1}{2}mv^2$ = $0.5 \times 25 \times (0.64)^2 = 5.1(2)$ J		C1 A1 [2]
	(ii) zero		A1 [1]
	(iii) $(-)$ 5.1(2) J		A1 [1]
	(b) (i) PE = $mgh$ = $350 \times 0.64 \times 25$ = 5600 J		C1 C1 A1 [3]
	(If full length used allow 1/3)		
	(ii) $P = Fv$ or gain in PE / $t$ , $E_p / t$ or work done / $t$ , $W / t$ = $350 \times 0.64$ or $5600 / 25$ = 220 (224) W		C1 A1 [2]
6	melting: solid to liquid at a specific/one temperature/at the melting point		B1 B1
	evaporation: liquid to vapour/gas OR molecules escape from surface of liquid at all temperatures		B1 B1 [4]

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	21

- 7 (a) due to the lost volts in internal resistance / cell or energy losses in the internal resistance / cell B1 [1]
- (b) (i)  $V = IR$  C1  
 $= 1.2 \times 6 = 7.2V$  A1 [2]
- (ii) p.d. across Y and internal resistance  $r = 4.8(V)$  [12 – 7.2] C1  
 resistance of Y +  $r = 4.8 / 1.2 = 4(\Omega)$  C1  
 resistance of Y =  $4 - 0.5 = 3.5 \Omega$  A1 [3]
- or
- $R_{\text{total}} = 12 / 1.2 = 10 (\Omega)$  (C1)  
 $X + r = 6.5 (\Omega)$  (C1)  
 resistance of Y =  $3.5 \Omega$  (A1)
- (iii)  $P = I^2 r$  C1  
 $= (1.2)^2 \times 0.5 = 0.72W$  A1 [2]
- (c) terminal p.d. increases as  $R$  is increased B1 [1]  
 current decreases so there are less lost volts
- 8 (a) two waves (of the same kind) travelling in opposite directions overlap B1  
 waves have same frequency / wavelength and speed B1 [2]
- (b) (i)  $T = 0.8(\text{ms})$  C1  
 $f = 1 / (0.8 \times 10^{-3}) = 1250(\text{Hz})$  A1 [2]
- (ii) microphone is moved from plate to loudspeaker or vice versa B1  
 wavelength is the twice the distance between adjacent maxima or minima (seen on c.r.o.) B1 [2]
- (iii)  $v = f\lambda$  C1  
 $= 1250 \times 0.26$   
 $= 330 (325)\text{ms}^{-1}$  A1 [2]